

INCALZIRE CU AER CALD

www.alke.ro



ALKE - Total Confort SRL

Member of ALKE GROUP

Solutii complete de incalzire

Generatoare de aer cald

Gama AKD

- * Puteri disponibile de la 36 la 92 kW, cu un debit de aer de la 2900 la 8000 m³/h;
- * Instalare simpla, sub tavan;
- * Admisia de aer se face din interiorul halei;
- * Jet de aer cald vertical;
- * Destratificare;
- * Arzator cu optiune de reglare a capacitatii de incalzire de la 70 la 100%;
- * Ventilator axial.



Model		AKD 36	AKD 45	AKD 55	AKD 75	AKD 95
Putere intrare	kW	36	45	55	71	92
Putere iesire	kW	32,5	40,5	50	64,4	84
Randament	%	>91	>91	>91	>91	>91
Debit aer 15°C	m ³ /h	2900	4000	4900	5800	8000
Δ t° aer	°C	33	30	30	32	31
Inaltime montaj (min/max)	m	4/6	5/8	5/10	6/12	6/12
Consum - gaz natural	m ³ /h	3,81	4,76	5,82	7,4	10
Presiune - gaz natural	mbar	20	20	20	20	20
Consum - propan	kg/h	2,81	3,51	4,3	5,46	7,4
Presiune - propan	mbar	37	37	37	37	37
Conexiune gaz		Ø 1/2"	Ø 1/2"	Ø 1/2"	Ø 3/4"	Ø 3/4"
Tubulatura evacuare aer	mm	80	100	130	130	130
Tubulatura admisie aer	mm	125	100	130	130	130
Conexiune electrica	230 V, monofazic					
Putere electrica	W	320	350	500	580	750
Greutate	kg	90	105	127	145	185
Nivel zgomot	dB	41	46	51	52	49

Dimensiuni		A	B	C
AKD 36	mm	810	820	510
AKD 45	mm	1040	820	570
AKD 55	mm	1040	840	700
AKX 75	mm	1120	840	820
AKX 95	mm	1120	840	1075

