

# INCALZIRE CU AER CALD

[www.alke.ro](http://www.alke.ro)



**ALKE - Total Confort SRL**

**Member of ALKE GROUP**

**Solutii complete de incalzire**

# Generatoare de aer cald

## Gama AKX

- \* Puteri disponibile de la 16 la 92 kW, cu un debit de aer de la 1350 la 8000 m<sup>3</sup>/h;
- \* Usor de instalat;
- \* Admisia de aer se face din interiorul halei;
- \* Distribuirea directa a aerului cald in hala de incalzit;
- \* Arzator cu optiune de reglare a capacitatii de incalzire de la 70 la 100%;
- \* Ventilator axial.



Model		AKX 16	AKX 20	AKX 28	AKX 35	AKX 45	AKX 55	AKX 75	AKX 95
Putere intrare	kW	16	21	28	35	45	55	71	92
Putere iesire	kW	14,5	19,5	25,5	31,5	40,5	50	64,4	84
Randament	%	>91	>91	>91	>91	>91	>91	>91	>91
Debit aer 15°C	m <sup>3</sup> /h	1350	1450	2050	2900	4000	4900	5800	8000
Δ t° aer	°C	32	40	36	32	30	30	32	31
Lungime jet aer	m	12	12	16	23	26	28	30	30
Consum - gaz natural	m <sup>3</sup> /h	1,69	2,22	2,96	3,7	4,76	5,82	7,4	10
Presiune - gaz natural	mbar	20	20	20	20	20	20	20	20
Consum - propan	kg/h	1,25	1,64	2,18	2,73	3,51	4,3	5,46	7,4
Presiune - propan	mbar	37	37	37	37	37	37	37	37
Conexiune gaz		Ø 1/2"	Ø 1/2"	Ø 1/2"	Ø 1/2"	Ø 1/2"	Ø 1/2"	Ø 3/4"	Ø 3/4"
Tubulatura evacuare aer	mm	80	80	80	80	100	130	130	130
Tubulatura admisie aer	mm	125	125	125	125	100	130	130	130
Conexiune electrica	230 V, monofazic								
Putere electrica	W	290	300	310	320	350	500	580	750
Greutate	kg	75	82	82	90	105	127	145	185
Nivel zgomot	dB	37	39	40	41	46	51	52	49

Dimensiuni		A	B	C
AKX 16	mm	810	780	356
AKX 20	mm	1040	800	460
AKX 28	mm	1040	820	460
AKX 35	mm	1040	820	510
AKX 45	mm	1040	820	570
AKX 55	mm	1040	840	700
AKX 75	mm	1120	840	820
AKX 95	mm	1120	840	1075

